

TECH SPEC JABRA PRO 900 SERIES

| Product Name | Jabra PRO 920 | Jabra PRO 930 | Jabra PRO 925 | Jabra PRO 935 |
|--|---|---|---|---|
| Packaging dimensions (L x W x H) | Mono master carton: 600 x 399 x 316mm Mono unit box: 185 x 138.5 x 67.5mm Duo master carton: 600 x 399 x 235mm Duo unit box: 190 x 191 x 65mm | Mono master carton: 600 x 399 x 316mm Mono unit box: 185 x 138.5 x 67.5mm Duo master carton: 600 x 399 x 235mm Duo unit box: 190 x 191 x 65mm | Master carton: 600 x 399 x 316mm Unit box: 185 x 138.5 x 67.5mm | Master carton: 600 x 399 x 316mm Unit box: 185 x 138.5 x 67.5mm |
| Main unit dimension (L x W x H) | Base: 118 x 76 x 29mm Mono headset: 131 x 50 x 18mm Duo headset: 165 x 165 x 30mm | Base: 118 x 76 x 29mm Mono headset: 131 x 50 x 18mm Duo headset: 165 x 165 x 30mm | Base: 118 x 76 x 29mm Headset: 131 x 50 x 18mm | Base: 118 x 76 x 29mm Headset: 131 x 50 x 18mm |
| Weight | Base: 177g Mono headset: 29g Duo headset: 80g | Base: 165g Mono headset: 29g Duo headset: 80g | Base: 177g Headset: 29g | Base: 165g Headset: 29g |
| What's in the box | 1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. USB cable (PRO 930 & 935 only) 9. Flat cable (PRO 920 & 925 only) | 1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. USB cable (PRO 930 & 935 only) 9. Flat cable (PRO 920 & 925 only) | 1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. USB cable (PRO 930 & 935 only) 9. Flat cable (PRO 920 & 925 only) | 1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. USB cable (PRO 930 & 935 only) 9. Flat cable (PRO 920 & 925 only) |
| Battery included | Yes | Yes | Yes | Yes |
| Charging time | 180 min | 180 min | 180 min | 180 min |
| AC power supply | Yes | Yes | Yes | Yes |
| Certifications | CE, CB, FCC, IC, NOM, NTC, EAC, PSB, ICASA, SIRIM, ACMA, NZ Telepermit, UL, TCO | CE, CB, FCC, IC, NOM, NTC, EAC, PSB, ICASA, SIRIM, ACMA, NZ Telepermit, UL, TCO | CE, FCC, IC, UL, SRRC, TELEC, EAC, NCC, IDA, RoHS, Reach, KCC, ETA, ACMA, EMC, SIRIM, NTC, DGPosTel | CE, FCC, IC, UL, SRRC, TELEC, EAC, NCC, IDA, RoHS, Reach, KCC, ETA, ACMA, EMC, SIRIM, NTC, DGPosTel |
| Warranty | North America: 1 year limited warranty Europe/APAC : 2 year limited warranty | North America: 1 year limited warranty Europe/APAC : 2 year limited warranty | North America: 1 year limited warranty Europe/APAC : 2 year limited warranty | North America: 1 year limited warranty Europe/APAC : 2 year limited warranty |
| Bluetooth® device | N/A | N/A | Yes | Yes |
| DECT Device | Yes | Yes | N/A | N/A |
| NFC | N/A | N/A | Yes (only on Dual connectivity) | Yes (only on Dual connectivity) |
| Operating range | Up to 120m/395ft | Up to 120m/395ft | Up to 100 meter/330ft | Up to 100 meter/330ft |
| Headset bandwidth | Narrowband and Wideband | Narrowband and Wideband | Narrowband and Wideband | Wideband only |
| Connection (mini jack, USB, etc) | Mini USB, RJ-9 for handset, RJ-9 for phone body, RJ-45 for AUX | Mini USB | Mini USB, RJ-9 for handset, RJ-9 for phone body, RJ-45 for AUX | Mini USB |
| Talk time | Up to 12 hours | Up to 12 hours | Up to 12 hours | Up to 12 hours |
| Standby time | Up to 33 hours | Up to 33 hours | Up to 7 days | Up to 7 days |
| What is Bluetooth® wireless technology | N/A | N/A | Bluetooth® version 4.0 | Bluetooth® version 4.0 |
| Speaker size | Mono: Ø 28 x 5.9mm Duo: Ø 23 x 6.2mm | Mono: Ø 28 x 5.9mm Duo: Ø 23 x 6.2mm | Ø 28 x 5.9mm | Ø 28 x 5.9mm |
| Speaker sensitivity | 91±3dB (60mV at 1000Hz) | 91±3dB (60mV at 1000Hz) | 91±3dB (60mV at 1000Hz) | 91±3dB (60mV at 1000Hz) |
| Speaker impedance | Mono: 32±4.8Ω (at 1000Hz) Duo: 64±1.5% Ohm at 1000Hz | Mono: 32±4.8Ω (at 1000Hz) Duo: 64±1.5% Ohm at 1000Hz | 32±4.8Ω (at 1000Hz) | 32±4.8Ω (at 1000Hz) |
| Speaker max output power | Mono: Max input Power 20mW at 0.8V Duo: Not specified | Mono: Max input Power 20mW at 0.8V Duo: Not specified | Max input Power 20mW at 0.8V | Max input Power 20mW at 0.8V |
| Speaker frequency range | Mono: 150Hz to 7 kHz (at output S.P.L. -10dB) Duo: 180Hz to 7 kHz | Mono: 150Hz to 7 kHz (at output S.P.L. -10dB) Duo: 180Hz to 7 kHz | 150Hz to 7 kHz (at output S.P.L. -10dB) | 150Hz to 7 kHz (at output S.P.L. -10dB) |
| Microphone type | Uni-directional Microphone | Uni-directional Microphone | Uni-directional Microphone | Uni-directional Microphone |
| Microphone sensitivity | -30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa) | -30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa) | -30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa) | -30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa) |
| Microphone frequency range | 100Hz to 10kHz | | | |

Extended Info

| | | |
|-------------------------------|-----|---|
| Supported Bluetooth® profiles | N/A | A2DP (v1.2), Handsfree Profile (v1.6), Headset Profile (v1.2), AGHFP (v1.6) |
| Bluetooth® compliance | N/A | Yes |

TECH SPEC JABRA PRO 900 SERIES

| Product Name | Jabra PRO 920 | Jabra PRO 930 | Jabra PRO 925 | Jabra PRO 935 |
|--------------------------------------|--|---------------------------------------|---|---|
| Bluetooth® wireless technology | N/A | N/A | Bluetooth® Class 1 (only on Dual connectivity) | Bluetooth® Class 1 (only on Dual connectivity) |
| Speaker bandwidth Speak mode | 20Hz-4.5kHz | 20Hz-4.5kHz | Not specified | Not specified |
| USB Cord length | 1.5m | 1.5m | 1.5m | 1.5m |
| Operating temperature | 0°C to 40°C (32°F to 104°F) | 0°C to 40°C (32°F to 104°F) | 0°C to 40°C (32°F to 104°F) | 0°C to 40°C (32°F to 104°F) |
| Storage temperature | -20°C to 45°C (-4°F to 113°F) | -20°C to 45°C (-4°F to 113°F) | -20°C to 45°C (-4°F to 113°F) | -20°C to 45°C (-4°F to 113°F) |
| Supported modes | N/A | N/A | SCO, eSCO, Sniff mode | SCO, eSCO, Sniff mode |
| Security | DSAA + DSC | DSAA + DSC | Authentication and Encryption (Bluetooth® standard) | Authentication and Encryption (Bluetooth® standard) |
| Power consumption | 7.5V/650mA | 7.5V/650mA | 7.5V/650mA | 7.5V/650mA |
| Current consumption microphone | 70 to 150 uA | 70 to 150 uA | 70 to 150 uA | 70 to 150 uA |
| Battery status % after 30 min/60 min | 25% after 30 min and 50% after 60 min | 25% after 30 min and 50% after 60 min | 25% after 30 min and 50% after 60 min | 25% after 30 min and 50% after 60 min |
| Charging plug dimensions | Ø 2.35mm | | | |
| Material used | Polycarbonate/ Akrylonitril-butadien-styren (PC/ABS): CYCOLOY C1200HF, GY6A288 Thermoplastic Polyurethanes - TPU: Desmopan 445 Acetal (POM) Copolymer: POM Tepcon M90 Thermoplastic acetal homopoly: DELRIN 500 P Polybutylene Terephthalate (PBT): PBT S600F20 Thermoplastic Elastomer (TPE): TPE Hytrel 4069 Thermoplastic Elastomer (TPE): TPE Hytrel 3548 Polypropylene (PP): AV161 Thermoplastic vulcanizates (TPVs): Santoprene TPV 201-87 Silicone rubber: KE-931TU | | | |
| Pairing PIN | N/A | N/A | 0000 | 0000 |
| Features | Crystal Clear Sound HD Voice – Wideband Audio Jabra Software Applications Noise Canceling Microphone PeakStop™ Remote Asset Management Remote Call Control SafeTone™ Talk in Comfort Up to 120 Meter/395ft Wireless Freedom (PRO 920 & 930) Up to 100 Meter/330ft Wireless Freedom (PRO 925 & 935) 8-Hour Battery Life UC Plug-And-Play (PRO 935 & 930) | | | |

| ITEM NUMBER | DESCRIPTION 1 | DESCRIPTION 2 | EAN | UPC |
|-------------------|--------------------------------|-------------------------------|---------------|--------------|
| 920-25-508-101 | Jabra PRO 920, EMEA | 1.88-1.9 GHz EU standard DECT | 5706991013566 | |
| 920-25-508-101JPM | Jabra PRO 920, EMEA JPM | Range set to Very Low | 5706991018516 | |
| 920-25-508-102 | Jabra PRO 920, UK/HK/SG | 1.88-1.9 GHz EU standard DECT | 5706991013573 | |
| 920-25-508-102JPM | Jabra PRO 920, UK JPM | Range set to Very Low | 5706991018509 | |
| 920-25-508-103 | Jabra PRO 920, AU/NZ | 1.88-1.9 GHz EU standard DECT | 5706991013580 | |
| 920-29-508-101 | Jabra PRO 920 Duo, EMEA | 1.88-1.9 GHz EU standard DECT | 5706991018318 | |
| 920-29-508-102 | Jabra PRO 920 Duo, UK/HK/SG | 1.88-1.9 GHz EU standard DECT | 5706991018325 | |
| 920-29-508-103 | Jabra PRO 920 Duo, AU/NZ | 1.88-1.9 GHz EU standard DECT | 5706991018332 | |
| 920-65-508-105 | Jabra PRO 920, NA | 1.92-1.93 GHz US DECT 6.0 | 5706991013597 | 706487012795 |
| 920-69-508-105 | Jabra PRO 920 Duo, NA | 1.92-1.93 GHz US DECT 6.0 | 5706991018349 | 706487016175 |
| 930-25-503-101 | Jabra PRO 930 MS, EMEA | 1.88-1.9 GHz EU standard DECT | 5706991013603 | |
| 930-25-503-102 | Jabra PRO 930 MS, UK/HK/SG | 1.88-1.9 GHz EU standard DECT | 5706991013610 | |
| 930-25-503-103 | Jabra PRO 930 MS, AU/NZ | 1.88-1.9 GHz EU standard DECT | 5706991013627 | |
| 930-25-509-101 | Jabra PRO 930, EMEA | 1.88-1.9 GHz EU standard DECT | 5706991013634 | |
| 930-25-509-101JPM | Jabra PRO 930, EMEA JPM | Range set to Very Low | 5706991018530 | |
| 930-25-509-102 | Jabra PRO 930, UK/HK/SG | 1.88-1.9 GHz EU standard DECT | 5706991013641 | |
| 930-25-509-102JPM | Jabra PRO 930, UK JPM | Range set to Very Low | 5706991018523 | |
| 930-25-509-103 | Jabra PRO 930, AU/NZ | 1.88-1.9 GHz EU standard DECT | 5706991013658 | |
| 930-29-503-101 | Jabra PRO 930 Duo MS, EMEA | 1.88-1.9 GHz EU standard DECT | 5706991018356 | |
| 930-29-503-102 | Jabra PRO 930 Duo MS, UK/HK/SG | 1.88-1.9 GHz EU standard DECT | 5706991018363 | |
| 930-29-503-103 | Jabra PRO 930 Duo MS, AU/NZ | 1.88-1.9 GHz EU standard DECT | 5706991018370 | |
| 930-29-509-101 | Jabra PRO 930 Duo, EMEA | 1.88-1.9 GHz EU standard DECT | 5706991018387 | |
| 930-29-509-102 | Jabra PRO 930 Duo, UK/HK/SG | 1.88-1.9 GHz EU standard DECT | 5706991018394 | |

| ITEM NUMBER | DESCRIPTION 1 | DESCRIPTION 2 | EAN | UPC |
|-------------------|--------------------------------------|-------------------------------|---------------|--------------|
| 930-29-509-103 | Jabra PRO 930 Duo, AU/NZ | 1.88-1.9 GHz EU standard DECT | 5706991018400 | |
| 930-65-503-105 | Jabra PRO 930 MS, NA | 1.92-1.93 GHz US DECT 6.0 | 5706991013665 | 706487012801 |
| 930-65-509-105 | Jabra PRO 930, NA | 1.92-1.93 GHz US DECT 6.0 | 5706991013672 | 706487012818 |
| 930-69-503-105 | Jabra PRO 930 Duo MS, NA | 1.92-1.93 GHz US DECT 6.0 | 5706991018417 | 706487016199 |
| 930-69-509-105 | Jabra PRO 930 Duo, NA | 1.92-1.93 GHz US DECT 6.0 | 5706991018424 | 706487016182 |
| 925-15-508-106 | Jabra PRO 925, China | Single Connectivity | 5706991016611 | 706487014607 |
| 925-15-508-107 | Jabra PRO 925, Korea | Single Connectivity | 5706991016628 | 706487014614 |
| 925-15-508-182 | Jabra PRO 925, HK, SG, MY, IN, ID | Single Connectivity | 5706991016635 | 706487014621 |
| 925-15-508-182 IN | Jabra PRO 925, IN | Single Connectivity | 5706991019445 | |
| 925-15-508-185 | Jabra PRO 925, JP,TW,TH,PH,VN,NA | Single Connectivity | 5706991016642 | 706487014638 |
| 925-15-508-201 | Jabra PRO 925 BT, EMEA | Dual Connectivity | 5706991016659 | 706487014645 |
| 925-15-508-202 | Jabra PRO 925 BT, UK, HK, SG | Dual Connectivity | 5706991016666 | 706487014652 |
| 925-15-508-203 | Jabra PRO 925 BT, AU, NZ | Dual Connectivity | 5706991016673 | 706487014669 |
| 925-15-508-205 | Jabra PRO 925 BT, NA | Dual Connectivity | 5706991016680 | 706487014676 |
| 925-15-508-206 | Jabra PRO 925 BT - CN | Dual Connectivity | 5706991017496 | |
| 925-15-508-207 | Jabra PRO 925 BT - KR | Dual Connectivity | 5706991017502 | |
| 935-15-503-106 | Jabra PRO 935 MS, China | Single Connectivity | 5706991016697 | 706487014683 |
| 935-15-503-107 | Jabra PRO 935 MS, Korea | Single Connectivity | 5706991016703 | 706487014690 |
| 935-15-503-182 | Jabra PRO 935 MS, HK, SG, MY, IN, ID | Single Connectivity | 5706991016710 | 706487014706 |
| 935-15-503-182 IN | Jabra PRO 935 MS, IN | Single Connectivity | 5706991019452 | |
| 935-15-503-185 | Jabra PRO 935 MS, JP,TW,TH,PH,VN,- | Single Connectivity | 5706991016727 | 706487014713 |
| 935-15-503-201 | Jabra PRO 935 MS, BT, EMEA | Dual Connectivity | 5706991016734 | 706487014720 |
| 935-15-503-202 | Jabra PRO 935 MS, BT, UK, HK, SG | Dual Connectivity | 5706991016741 | 706487014737 |
| 935-15-503-203 | Jabra PRO 935 MS, BT,AU, NZ | Dual Connectivity | 5706991016758 | 706487014744 |
| 935-15-503-205 | Jabra PRO 935 MS, BT, NA | Dual Connectivity | 5706991016765 | 706487014751 |
| 935-15-503-206 | Jabra PRO 935 MS BT - CN | Dual Connectivity | 5706991017533 | |
| 935-15-503-207 | Jabra PRO 935 MS BT - KR | Dual Connectivity | 5706991017540 | |
| 935-15-509-106 | Jabra PRO 935, CN | Single Connectivity | 5706991016772 | 706487014768 |
| 935-15-509-107 | Jabra PRO 935 Korea | Single Connectivity | 5706991016789 | 706487014775 |
| 935-15-509-182 | Jabra PRO 935, HK, SG, MY, IN, ID | Single Connectivity | 5706991016796 | 706487014782 |
| 935-15-509-182 IN | Jabra PRO 935, IN | Single Connectivity | 5706991019469 | |
| 935-15-509-185 | Jabra PRO 935, JP,TW,TH,PH,VN,NA | Single Connectivity | 5706991016802 | 706487014799 |
| 935-15-509-201 | Jabra PRO 935 BT, EMEA | Dual Connectivity | 5706991016819 | 706487014805 |
| 935-15-509-202 | Jabra PRO 935, BT, UK,HK,SG | Dual Connectivity | 5706991016826 | 706487014812 |
| 935-15-509-203 | Jabra PRO 935 BT, AU, NZ | Dual Connectivity | 5706991016833 | 706487014829 |
| 935-15-509-205 | Jabra PRO 935 BT, NA | Dual Connectivity | 5706991016840 | 706487014836 |
| 935-15-509-206 | Jabra PRO 935 UC BT - CN | Dual Connectivity | 5706991017519 | |
| 935-15-509-207 | Jabra PRO 935 UC BT - KR | Dual Connectivity | 5706991017526 | |