

# Poly Trio C60 IP Conference Phone Full Radio and PoE-enabled

One device. Many possibilities.

Bring people together. Launch big ideas. And make sure everyone at the table can be heard, near or far with Poly signature audio. The Trio C60 plays nicely with everyone, delivering native experiences on your favorite collaboration platforms.



\*Product image may differ from actual product

## Poly signature audio

Get more out of your conference calls. Poly reduces distracting background noise to ensure every inflection is heard. Hear every reaction with up to 22 kHz of rich, full sound.

## One-touch join

All it takes is a fingertip to get started. Join your calls in a second with a single touch of a button thanks to the truly intuitive user experience.

## Flexible connectivity

Maximize flexibility and investments with connectivity to multiple SIP and UC-cloud services simultaneously.

## Audio clarity

Experience the power of full-duplex audio for natural conversations. Count on audio clarity in any size space with echo and reverb cancellation.

## Poly portfolio compatible

Complement your Poly Studio X50, Poly Studio X30, or G7500 video solution with fast, simple control from Trio C60.

## Scalable

Cater to any size meeting with optional expansion microphones or by daisy-chaining multiple systems together.

Datasheet

# Poly Trio C60 IP Conference Phone Full Radio and PoE-enabled

## Specifications



### Display

**Aspect ratio:** 16:9  
**Native resolution:** 720 x 1280  
**Panel technology:** Color LCD  
**Display size (diagonal):** 5"  
**Display size (diagonal, metric):** 12.7 cm (5")  
**Touch-enabled:** Gesture-based, multi-touch capable touchscreen

### Connectivity and communications

**Wireless range:** Up to 6.1 m  
**Wireless range (Imperial):** Up to 20 ft  
**External I/O ports:**  
 1 USB 2.0 Type-A (for USB battery charging)  
 1 USB 2.0 Micro-B (for USB audio device)  
 2 RJ-45 (10/100/1000BASE-TX Mbps)  
**Wireless technologies:**  
 Bluetooth® 4.2  
 Wi-Fi network connectivity: 2.4-2.4835 GHz (802.11b, 802.11g, 802.11n HT-20)  
 5.15-5.825 GHz (802.11a, 802.11n, HT-20, 802.11n HT-40)

### Battery

**Power features:**  
 LAN IN: Built-in auto-sensing IEEE 802.3at, PoE Device (Class 4)  
 LAN OUT: Built-in auto-sensing IEEE 802.3af power sourcing equipment<sup>1</sup>

### User interface features

**Languages:**  
 Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Portuguese; Romanian; Russian; Slovenian; Spanish; Swedish

### Audio

**Audio features:**  
 Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression  
 Comfort noise generation  
 DTMF tone generation (RFC 2833 and in-band)  
 Low delay audio packet transmission  
 Adaptive jitter buffers  
**Microphone type:** Three cardioid microphones  
**Frequency response (microphone):** 100 Hz to 22 kHz  
**Sensitivity (speaker):** 92 dB  
**Audio codecs:**  
 G.711 (A-law and μ-law)  
 G.722  
 G.722.1  
 G.722.1C  
 G.729AB  
 G.719  
 Polycom® Siren™ 7  
 Siren™ 14  
 iLBC  
 OPUS

### Environmental

**Certifications and compliances:** AS/NZS 60950-1; AS/NZS 62368-1:17; Australia -AS/NZ4268; Australia A&C Tick; CAN/CSA C22.2 No. 60950-1-03; CAN/CSA C22.2 No. 62368-1:14; CE Mark; CISPR22 Class B; EN 301 489-1, EN 301 489-3, EN 301 489-17; EN 61000-3-2; EN 61000-3-3; EN 62368-1; ETSI EN 300 328 v1.9; ETSI EN 300 330; ETSI EN 301 893 v1.7; FCC Part 15 (CFR 47) Class B; FCC Part 15.225; FCC Part 15.247; FCC Part 15.407; ICES-003 Class B; IEC 60950-1; IEC 62368-1; Japan Item (19); Japan Item (19)-3; Japan Item (19)-3-2; Japan MIC/VCCI Class B; NZ Telepermit; ROHS compliant; RSS 247 Issue 1; UL 60950-1; UL 62368-1  
**Operating humidity range:** 5 to 95%  
**Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit):** 0 to 40°C / 32 to 104°F  
**Storage temperature range (Celsius) / Storage temperature range (Fahrenheit):** -20 to 70 °C / -40 to 158°F  
**Energy star certified:** ENERGY STAR® certified

### Certifications

**Certified collaboration software:** Microsoft Teams; Skype for Business; Zoom  
**Special features:**  
 Unicode UTF-8 character support

### Applications supported

**Management software:**  
 Poly Zero Touch Provisioning  
 RealPresence Resource Manager (v. 10.1 or above) based provisioning  
 Polycom Device Management Service for Enterprise (PDMS-E)  
 Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management  
 SDP

### Display features

On-screen virtual keyboard

### Security

**Security management:**  
 802.1X Authentication and EAPOL Media encryption via SRTP  
 Digest authentication  
 Encrypted configuration files  
 HTTPS secure provisioning  
 Password login  
 Support for signed software executables  
 Support for URL syntax with password  
 Transport Layer Security (TLS)  
 Wi-Fi encryption: WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2)  
 FIPS 140-2 compliant cryptographic module

### Network

**Supported network protocols:**  
 DHCP VLAN discovery  
 LLDP-MED for VLAN discovery  
 FTP/TFTP/HTTP/HTTPS server-based central provisioning  
 Manual or dynamic host configuration protocol (DHCP) network setup  
 QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP  
 Time and date synchronization using SNTP  
 Provisioning and call server redundancy support  
**VoIP features:**  
 IETF SIP (RFC 3261 and companion RFCs)

# Poly Trio C60 IP Conference Phone Full Radio and PoE-enabled

## Specifications



### Headset and handset compatibility

**Headset and handset compatibility:**  
Bluetooth® headset compatibility

### Telephony and call handling features

**Telephony and call handling features:**  
Bundled with Polycom UC Software: Corporate Directory Access using LDAP  
Call timer and call waiting  
Call transfer, hold, divert (forward), park, pickup  
Called, calling, connected party information  
Distinctive incoming call treatment/call waiting  
Do not disturb function  
Local configurable digit map/dial plan  
Local five-way audio conferencing  
Shared call/bridged line appearance  
Visual Conference Management  
Up to 3 lines (maximum one Skype for Business and Microsoft Teams)  
Daisy-chain up to four  
One-touch speed dial, redial and meeting join

### Weight and dimensions

**Product Primary Color:** Black  
**Weight (Imperial):** 2.1 lb  
**Weight (metric):** 950 g  
**Product dimensions (Imperial):** 15.1 x 2.9 x 13.1 in  
**Product Dimensions (metric):** 38.3 x 7.5 x 33.2 cm  
**Package dimensions (Imperial):** 19 x 4.5 x 15.5 in  
**Package dimensions (metric):** 48.3 x 11.5 x 39.4 cm  
**Package weight (Imperial):** 4.3 lb  
**Package Weight (metric):** 1970 g  
**UPC number:** 197497506457  
**Product number:** 849B4AA

### Warranty

Poly standard one-year limited warranty

### What is in the box

Console  
Network (LAN) cable-CAT-5E  
USB Type-A cable  
Cable wrap  
Tactile overlay for improved accessibility  
Setup sheet

### Technical Specifications Footnotes

<sup>1</sup> Requires full Class 4 power input on LAN IN for operation