Connecting your Business

SNOM

M5





DECT single-cell/multi-cell range extender

The repeater increases the reception range of individual bases and handsets and bridges the gaps between base stations, increasing the free movement between base stations in a single seamless network

and allowing calls to continue uninterrupted. The M5 repeater offers superior audio quality in both wideband and narrowband calls.



Technical specification

SN()M

Basics

- Product information
 - DECT repeater | black | PN 00003930
- Placement: indoor, desktop, wall mounting
- Antenna diversity: 2 internal omni-directional antennas

Dimensions and weight

- Dimensions (H x W x D, approx.)
 - 129 mm × 118 mm × 33 mm
- Weight (approx.)
 - DECT repeater: 126 g
 - Power adapter: 120 g

Indicators and keys

- Multi-purpose status indication: 1 dual-colour LED
- 1 dedicated function key: Reset

Interfaces and connections

- Power options
 - Power adapter: 100 240 V AC / 50 60 Hz | 5.5 V DC / 600 mA
- Wired interfaces
 - Power adapter: coaxial power connector (socket)
- Wireless interfaces
 - DECT¹

DECT technology and features

- Standard: DECT
 - Authentication/encryption of base and handset
 - Seamless handover
 - Wideband audio
 - 12 time slots
 - Slot multiplexing
 - Slot packing
 - Full slot move over request
 - Receiver sensitivity: -92 dBm
- Frequency band
 - Europe: 1,880 1,900 MHz

- Latin America: 1,910 1,930 MHz
- USA: 1,920 1,930 MHz
- Output power
 - Level (dbm): 14, 17, 20, 24
- Coverage
 - Up to 50 m indoor range
 - Up to 100 m outdoor range
- Simultaneous calls per repeater
 - Wideband calls: up to 2
 - Narrowband calls: up to 5
- Auto registration when not registered

Package contents

- Hardware
 - DECT repeater
 - Power adapter
 - Power adapter clips
- Documentation
 - Quick Installation Guide



 1 DECT devices manufactured for the USA and Canada are marketed as DECT 6.0 2 Up to FW < 610.x

Disclaimer

Further information: Snom M5 webpage | Snom Service Hub | Type approval | Warranty information | Company locations

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.