

# UniFi Network

Datasheet  
UDM-SE

## Dream Machine Special Edition



## Mechanical

Dimensions	442.4 x 43.7 x 285.6 mm (17.4 x 1.7 x 11.2")
Weight	4.95 kg (10.9 lb)
Enclosure materials	Aluminium CNC, SGCC steel
Mount material	SGCC steel

## Hardware

Processor	Quad-core ARM® Cortex®-A57 at 1.7 GHz
System memory	4 GB DDR4
On-board storage	16 GB eMMC Integrated 128 GB SSD
Management interface	Ethernet Bluetooth
Networking interface	(8) LAN: GbE RJ45 ports (1) WAN: 2.5 GbE RJ45 port
SFP+ interface	(1) LAN: 10G SFP+ (1) WAN: 10G SFP+
PoE interface	(6) PoE (Pair A 1, 2+; 3, 6-) (2) PoE+ (Pair A 1, 2+; 3, 6-)
IDS/IPS throughput	3.5 Gbps* <small>*Measured with iPerf3</small>
Power method	(1) Universal AC input, 100–240V AC, 4.4A Max., 50/60 Hz (1) USP-RPS DC input, 52V DC, 3.94A
Power supply	AC/DC, internal, 240W
Supported voltage range	100–240V AC
Max. power consumption	50W (Excluding PoE output)
Max. PoE wattage per port by PSE	PoE: 15.4W PoE+: 30W
Voltage range PoE mode	PoE: 44–57V PoE+: 50–57V
ESD/EMP protection	Air: ± 15kV, contact: ± 8kV
LCM display	(1) 1.3" touchscreen
Button	Factory reset
Operating temperature	-10 to 40° C (14 to 104° F)
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

## LEDs

Ethernet	White: link/activity
SFP+	White: link/activity
HDD	White: disk activity Amber: disk error



